≮INEXGO

N92

New Generation Octa-core Pushing the boundaries to help you achieve more

The N92 boasts a stylish and superior design, along with high reliability. Not only that, it offers powerful performance with a 2.0 GHz octa-core processor and the Android 13 operating system. The N92 also features a robust power system, providing an impressive standby time of up to 280 hours.

Features

Performant Octa-core Processor &

Android 13

- Reliability
 1.2-meter Drop Protection
- Power-Efficient

2GB+32GB

280+ Hours Standby







280+ Hours Standby





ONEXCO

A : 8th Floor, Jialian Payment Building, Science and Technology South 12th Road No. 20, Nanshan District, Shenzhen, Guangdong, China

INEXEd

98889 88889 8888

N92 New Generation Octa-core Smart POS









Contactless/NFC

Magstripe Cards

IC Cards

1D&2D Codes

Specifications

OS Android 13	Processor Octa-Core 2.0GHz Processor Security Chip	Memory 2GB RAM + 32GB ROM (Micro SD Card Supported, up to 256GB)
Display 6.5"HD Color Screen,1600*720 Capacitive Touchscreen, Multi-Touch Customer Display 2.4" IPS,320*240 (Optional)	Keys 1 Power Key, 1 Shortcut key	Printer High Speed Thermal Printer, Roll Width: 58mm, Diameter: 40mm Up to 100mm/s
Card Readers Magnetic Stripe Cards Chip Cards Contactless Cards	Ports 1 x Type-C OTG, 1 x SD3.0; 1 x SIM + 2 x SAM, Or 2 x SIM+1 x SAM(Optional)	Communication 4G/3G/2G Wi-Fi, 802.11a/b/g/n/ac, 2.4GHz&5GHz BT5.0
PIN Pad Software PIN Pad Blind PIN Supported	Cameras Front: No Camera or 2MP FF Rear:2MP FF or 5MP AF with Flashlight	Positioning GPS, GLONASS or BEIDOU
Adaptor USB Type C 5V/2A USB Type C 5V/3A 15W Fast charge (Optional)	Battery 7.2V/2600mAh 7.2V/3300mAh(Optional)	Accessories Charging Base(Optional) Wireless Docking Station(Optional) Pro Scanner(Built-in)(Optional) Fingerprint Module(Optional)
Audio Built-in Speaker	Environmental Operating Temperature: -10°C to 50°C (Non-charge) Storage Temperature:	Certifications CE,ATEX, IP54; ROHS/WEEE; EMV3.0, L1&L2, Quickpass, Paypass,
Physical 188mm(L)*81mm(W)*68mm(H) 465g(Including Battery)	-20°C to 70°C Relative Humidity: 5% to 95%(Non-Condensing)	Paywave, JCB, AMEX, Discover, TQM; PCI6.X;