# NEXGO K206

Version 1.1 Issued February 2021

#### **NEXGOGLOBAL.COM**

© 2021 NEXGO | The information contained in this document is subject to change without notice. All pictures shown are for illustration purpose only, actual product and software may vary. NEXGO and the NEXGO logo are either trademarks or registered trademarks of NEXGO in the China and/or other countries. All other trademarks or brand names are the properties of their respective holders.









### Most Recommended Cost-Effective mPOS



K206 is the most recommended high cost-effective mPOS of NEXGO, it has passed the latest industry certifications including PCI 6.x. Only weighs 109 g, K206 is much smaller than your palm, users can take it anywhere.

## **Cost-Effective**

Most Recommended

PCI 6.x

**The Latest Secure Standard** 

mPOS

NEXGO

In Your Pocket



# Multifunctional

Through Bluetooth connection to the mobile app, K206 can support the payments of magnetic strip cards, IC cards, contactless/NFC .



Magnetic Strip Cards

contactless/NFC



IC Cards



# PCI 6.x Approved

K206 has passed the certification of PCI 6.x, it represents the latest payment card industry (PCI) security standards.

### **More Certifications**

NEXGO

K206

PCI 6.X

F2

F1

4<sub>GHI</sub> 5<sub>JKL</sub> 6<sub>MNO</sub>

1 qz.

 $7_{\text{PRS}}$ 

2 ABC 3 DEF

8<sub>тиν</sub> 9<sub>wxy</sub>







# mPOS in Your Pocket

The compact design of K206 can fully meet the requirements of users for portability with the size of 119 x 65 x 21 mm.

**109 g** Weight (Battery Included)



### K206 mPOS

Operating System Nexgo OS Processor Cortex-M4+M0 120MHz	<b>Card Readers</b> Magstripe Cards : Track 1/2/3, Bi-Directional Smart Cards : EMV & PBOC Approved Contactless Cards : 13.56MHz, ISO14443, Type-A/B. EMV, QPBOC Approved
<b>Memory</b> 4MB FLASH+256KB RAM	<b>Peripheral Ports</b> Type C
<b>Display</b> (128 x 64) LCD with Backlight	<b>Communication</b> Bluetooth, USB
<b>Keypad</b> 10 Function Keys 10 Numeric Keys	<b>PIN Pad</b> Built-in PIN Pad
	<b>Battery</b> 3.7V, 500mAh USB (Optional 5V/1A Charger)

#### Physical

119mm L x 65mm W x 21mm H 109g (Battery Included)

#### Environmental

Operating Temperature : 0° C to 50° C Storage Temperature : -20° C to 70° C Relative Humidity : 5% to 95%(Non-Condensing)

#### MTTF

> 50000 Hours

#### Security

PCI 6.x Approved



# THANK YOU!



