

Ethernet

T6 All-in-one Desktop and Portable POS Terminal







Contactless/NFC

Magstripe Cards

IC Cards

Specifications

Operating System Linux4.4.X	Display 3.5", 320*480 capacitive touch screen 1.9" Customer B&W Screen (Optional)	Card Slots SIM x 2 PSAM x 2 SD x 1
Processor Quad-Core Processor Cortex-A35 1.3GHz	Printer High Speed Thermal Printer	Keypad 16 Keys (Numeric/ Letter/ Function/ Power)
Memory 256MB FLASH +256MB DDR 512MB FLASH +512MB DDR (Optional)	Peripheral Ports 1 x TYPE-C USB, 1 x TYPE-A USB 1 x Ethernet, 1 x PINPAD/RS232 1 x Telephone line (Optional)	Contactless Cards 13.56MHz ISO14443 Type A/B
Battery (Optional) 3.7V/2600mAh	Communication Ethernet, 3G/2G (Optional) Wi-Fi (Optional), Modem (Optional)	Voltage 9.0V – 2.0A 5.5mm DC plug
Magstripe Cards Bi-Directional, Track 1/2/3 ISO7812	Environmental Operating Temperature: 0 to 50°C Storage Temperature: -20°C to 70°C Relative Humidity: 5% to 95% (Non-Condensing)	Audio Buzzer Speaker (Optional)
IC Cards ISO7816 Compatible with 1.8V/3V/5V Cards		