NEXGO G25

Version 1.0 Issued February 2023

NEXGOGLOBAL.COM

© 2023 NEXGO | The information contained in this document is subject to change without notice. All pictures shown are for illustration purpose only, actual product and software may vary. NEXGO and the NEXGO logo are either trademarks or registered trademarks of NEXGO in the China and/or other countries. All other trademarks or brand names are the properties of their respective holders.





G25

Traditional Portable POS Terminal



G25 is a NEXGO new generation traditional portable POS terminal. Its amazing exterior design, tough casing and a variety of functions could meet various business demands and provide perfect mobile payment solution.

ARM CORTEX A7 1.2GHz

Performance Communication

4G/3G/2G/Wi-Fi

Camera

0.3M Rear Camera

Support extensive payment methods

All payment methods like magnetic stripe cards, IC cards, contactless card, E-wallet, 1D & 2D barcodes could be supported on this terminal.



Contactless/NFC



Magstripe Cards



IC Cards



1D&2D Codes



Amazing exterior design and tough casing

Its friendly structural design makes this terminal comfortable to hold and it could pass 1.2m drop down test.





0.3MP Rear Camera

Optional 0.3MP rear camera could read 1D&2D code data, and it brings convenient on payment and reading commodity data.









Fast Printing

The high speed thermal printer of G25 could support 58mm width and 40mm diameter paper roll.







G25 Portable POS Terminal

Operating System Linux	Printer High Speed Thermal Printer Paper Roll Width: 58mm Diameter: 40mm	Communication 4G/3G/2G, Wi-Fi	Physical 175mm L x 80mm W x 62mm H 370g
Processor ARM CORTEX-A7 1.2GHz Memory	Card Readers Magstripe Cards: Track 1/2/3, Bi- Directional Smart Cards: EMV L1 & L2 Approved Contactless Cards: 13.56MHz, ISO14443, Type A/B, EMV L1 & L2; Paypass and Paywave Approved	Peripheral Ports 1 x Type-C USB 1 x DC Port (Optional)	Keypad 10 Numeric Keys, 6 Function Keys Dustproof Built-in Password Keyboard
Display 2.8", 320 * 240 TFT Color Screen; Adjustable Backlight Resistive Touchscreen (Optional)		Card Slots 1 X PSAM, 2 X SIM 1 x SIM+2 x PSAM (Optional)	Environmental Operating Temperature: 0° C to 50° C Storage Temperature: -20° C to 70° C Relative Humidity: 5% to 95% (Non-Condensing)
	Audio Buzzer	Camera(Optional) Rear Camera: 0.3MP FF	
Battery 3.7V/2600mAh	Voltage Input: 100 - 240V, 50-60Hz, 0.3A Output: 5V/1A	Biometrics (Optional) Fingerprint Identification	Certifications PCI6.X, CE, EMV L1/L2, EMV CL L1, Paypass, Paywave etc.



THANK YOU!

